

DRIVE PPH25RR ★★★

Output 25 kW



Freedom of movement thanks to remote control. All remote control functions are adjustable



Three-way switch, secondary connections, operating hours counter



Plastic cover can be removed without tools

The 4-stage control ensures optimal cutting speeds for all applications and the potentiometer of the remote

control ensures a wire-conserving smooth start/soft start.

System & Accessories



Technical data

Electric motor

| | |
|--------|-------|
| Output | 25 kW |
|--------|-------|

Hydraulics

| | |
|-----------------|--------------------|
| Pressure stages | 4 |
| 2 feed circuits | Radial piston pump |
| Main circuit | Triple gear pump |

Output

| | |
|---------|---------------------|
| Stage 1 | 45 l/min at 230 bar |
| Stage 2 | 50 l/min at 200 bar |
| Stage 3 | 60 l/min at 170 bar |
| Stage 4 | 70 l/min at 140 bar |

Electrical equipment

| | |
|----------------------------------------------------------------------|-----------------------|
| Voltage | 380 V / 400 V / 480 V |
| Frequency | 50 Hz / 60 HZ |
| Current consumption (400 V / 50 Hz) | 42 A |
| 2 secondary connections, (230 V / 50 Hz / 10 A (400 V / 50 Hz only)) | |

Dimensions

| | |
|--------|----------|
| Length | 760 mm |
| Width | 550 mm |
| Height | 1,140 mm |
| Weight | 170 kg |

System & Accessories

Drive unit PPH25RR***

| | |
|-----------|------------------------------------------------------|
| 10983900* | Drive unit PPH25RRP / 380-420V / 50Hz / Freq. 434MHz |
| 976206 | Hose package 5pieces 8 m FD |
| 975672 | Hose package 2pieces 8 m FF (feed) |

Accessories

| | |
|--------|-----------------------|
| 973074 | El.-plug CEE 63/5pol. |
|--------|-----------------------|

* Different voltage and frequency types are available upon request.